



FIBERGLASS SPECS.

<b>16 oz Salmon Neoprene Coated Fiberglass</b>				
1	CHARACTERISTIC		164050P	
2	WEAVE		PLAIN	
3	YARN (tex)	WARP WEFT	EC9 68 1X3 EC9 68 1X3	ECG 75 1/3 ECG 75 1/3
4	WIDTH		100 cm 150 cm	40 inch 60 inch
5	THICKNESS		0.53 mm	0.021 inch
6	COAT STYLE		DOUBLE NEOPRENE RUBBER (130g)	
7	CLOTH WEIGHT		400 g/m <sup>2</sup>	11.8 OZ/YD <sup>2</sup>
8	THREAD COUNT	WARP WEFT	18 per cm 13 per cm	45 per inch 33 per inch
9	TENSILE STRENGTH MIN	WARP WEFT	6000 N/ 5cm 4500 N/ 5cm	660 lbs/inch 495 lbs/inch
10	SERVICE TEMPERATURE		550°C/1022°F	

FM 4950 ANSI Approved

6205 BOAT ROCK BLVD  
ATLANTA, GA 30336  
404-699-9900 1800-445-2152  
FAX: 404-699-7800

880 SOUTH ROACH ST  
JACKSON, MS 39201  
1-800-647-7144  
FAX: 601-353-4848

937 AVENUE N  
GRAND PRAIRIE, TX 75050  
972-623-2571  
FAX: 972-623-2510

1210 AIRBRAKE AVE.  
TURTLE CREEK, PA 15145  
1-877-286-1868  
FAX: 412-357-2181

5910 W BY NW BLVD  
HOUSTON, TX 77040  
877-674-5586  
FAX: 832-308-1985