



FIBERGLASS 60"X50 YARDS SPECS.

FIBERGLASS 60" X 50 YRDS				
1	CHARACTERISTIC		185060	
2	WEAVE		PLAIN	
3	YARN (tex)	WARP WEFT	ET9 430 Tex ET9 430 Tex	ETG 11.6 ETG 11.6
4	WIDTH		100 cm 150 cm 180 cm	40 inch 60 inch 72 inch
5	THICKNESS		0.75 mm	0.03 inch
6	WEIGHT		600 g/m ²	17.6OZ/YD ²
7	THREAD COUNT	WARP WEFT	8 per cm 5.7 per cm	20 per inch 14 per inch
8	TENSILE STRENGTH MIN	WARP WEFT	2250 N/ 5cm 1216 N/ 5cm	250 lbs/inch 135 lbs/inch
9	SERVICE TEMPERATURE		550°C /1022°F	

NOTE: Support temp up to 1200°
 18oz Heat Cleaned Fiberglass
 No Coating

REMARKS:

- Used as welding blanket, mainly as tapestry
- Used as lining material of the insulation products
- Coated several coating, such as aluminum, silicon, and son on
- Established guidelines in the field will dictate performance

FM 4950 ANSI Approved

6205 BOAT ROCK BLVD
 ATLANTA, GA 30336
 404-699-9900 1800-445-2152
 FAX: 404-699-7800

880 SOUTH ROACH ST
 JACKSON, MS 39201
 1-800-647-7144
 FAX: 601-353-4848

937 AVENUE N
 GRAND PRAIRIE, TX 75050
 972-623-2571
 FAX: 972-623-2510

1210 AIRBRAKE AVE.
 TURTLE CREEK, PA 15145
 1-877-286-1868
 FAX: 412-357-2181

5910 W BY NW BLVD
 HOUSTON, TX 77040
 877-674-5586
 FAX: 832-308-1985